

## GENERAL CONDITIONS

1. CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS REQUIRED BY GOVERNING AUTHORITIES.
2. CONTRACTOR SHALL BE RESPONSIBLE FOR JOBSITE SAFETY. CONTRACTOR SHALL MAINTAIN LIABILITY AND WORKER'S COMPENSATION INSURANCE AS REQUIRED BY THE CONTRACT.
3. CONTRACTOR SHALL FURNISH CLIENT WITH WAIVERS OF LIEN AS THE WORK PROGRESSES (AT NO GREATER THAN ONE MONTH INTERVALS) AS PROOF OF PAYMENT TO SUBCONTRACTORS AND SUPPLIERS.
4. CONTRACTOR SHALL PROVIDE ALL NECESSARY TEMPORARY FACILITIES AND SERVICES REQUIRED DURING THE WORK INCLUDING BUT NOT LIMITED TO WASTE COLLECTION AND REMOVAL. PORTABLE TOILET TEMPORARY UTILITIES AND ENCLOSURES. ALL TRASH AND DEBRIS SHALL BE REMOVED OFFSITE AND LEGALLY DISPOSED OF.
5. CONTRACTOR SHALL MAKE ARRANGEMENTS WITH LOCAL SERVING UTILITIES FOR PERMANENT ELECTRICAL, WATER, SANITARY AND TELEPHONE SERVICE.
6. CONTRACTOR SHALL BE RESPONSIBLE FOR BUILDING LAYOUT AND CONFIRMATION AND ESTABLISHMENT OF BENCHMARK(S).
7. CONTRACTOR SHALL BE RESPONSIBLE FOR CONFIRMING ALL FIELD CONDITIONS AND FIELD MEASUREMENTS PRIOR TO ORDERING, FABRICATING, AND INSTALLING MATERIALS AND EQUIPMENT. CONTRACTOR TO ARRANGE AND COORDINATE WITH LOCAL UNDERGROUND UTILITY TRACKING COMPANY TO CONFIRM ALL UNDERGROUND LINES, PIPES, ETC.
8. ALL WORK SHALL BE INSTALLED STRAIGHT, PLUMB, AND TRUE AND IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND INDUSTRY STANDARDS.
9. CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING ALL WORK IN ACCORDANCE WITH ALL APPLICABLE BUILDING CODES.
10. THE INSTALLED WORK SHALL BE PROTECTED FROM DAMAGE OR ABUSE DURING THE COURSE OF CONSTRUCTION. THE FACILITY AND SYSTEMS SHALL BE CLEANED AND CHECKED FOR PROPER OPERATION PRIOR TO SUBSTANTIAL COMPLETION AND/OR CERTIFICATE OF OCCUPANCY.

## GENERAL PRODUCT INFORMATION

1. ALL MATERIAL SHALL BE NEW AND OBTAINED FROM A SINGLE SOURCE FOR A PARTICULAR PRODUCT.
2. ALL MATERIALS AND SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH THE PRODUCT OR SYSTEM MANUFACTURER'S RECOMMENDATION.
3. PROVIDE ALL FASTENERS, TRIM AND ACCESSORIES REQUIRED FOR A COMPLETE AND OPERATIONAL SYSTEM. FASTENER TYPE SHALL BE APPROPRIATE FOR THE MATERIAL AND SUBSTRATE.
4. THE CONTRACTOR SHALL SUBMIT PRODUCT DATA, SHOP DRAWINGS & OTHER DATA ONLY FOR MATERIALS AND FABRICATIONS INDICATED FOR REVIEW BY THE ARCHITECT PRIOR TO ORDERING & INSTALLING.

## SITework & LANDSCAPING

1. CONTRACTOR SHALL PROVIDE A LEVEL AND PREPARED BUILDING PAD IN PREPARATION FOR THE CONSTRUCTION. THE SITE SHALL BE GRADED TO ENSURE POSITIVE DRAINAGE AWAY FROM AND AROUND THE BUILDING.
2. ALL DISTRIBUTED GROUNDS SURROUNDING THE BUILDING & ROADWAYS SHALL BE FINE GRADED TO INSURE POSITIVE DRAINAGE AWAY FROM BUILDING & ROAD TO AVOID PONDING.

## ROUGH CARPENTRY

### 1. FRAMING

#### A. BLOCKING & BRIDGING

(1) STUD WALLS: PER APPLICABLE BUILDING CODE. FULL HEIGHT WALLS SHALL HAVE CONTINUOUS STUDS FROM BOTTOM TO TOP PLATE.

(2) CEILING JOISTS: PER APPLICABLE BUILDING CODE. USE SOLID BRIDGING.

(3) BACKING: PROVIDE SOLID BACKING AT ALL PENDANT OR SURFACE-MOUNTED ELECTRICAL FIXTURES, RAILS, GRAB BARS, BATH ACCESSORIES, ETC.

#### B. FIRE STOPPING: PER APPLICABLE BUILDING CODE.

C. STUD WALLS: PER APPLICABLE BUILDING CODE. ALL STUDS TO BE SIZED PER REQUIREMENTS OF CODE.

D. USE CONTINUOUS, FULL HEIGH STUDS IN ACORDANCE WITH THE HIGHEST STANDRDS OF CONSTRUCTION AND FRAMING PRACTICES.

E. BUILT-UP ROOFS, WATERPROOF BALCONY DECKS AND EXTERIOR HORIZONTAL AREAS ARE TO BE FRAMED WITH POSITIVE SLOPE AWAY FROM BUILDING TO ENSURE PROPER DRAINAGE WITHOUT PONDING.

F. PROVIDE BLOCKING WHERE REQUIRED TO PROVIDE A UNIFORM SURFACE WHERE FLUSH JOINTS AND BEAMS ARE DIFFERENT DEPTHS.

G. USE MITERED JOINTS AT FASCIA SPLICES (U.N.O.)

H. ALL DIMENSIONS TO EXTERIOR WALLS ARE GIVEN FROM INSIDE OR OUTSIDE OF ROUGH FRAMING, U.N.O. ALL DIMENSIONS TO INTERIOR PARTITIONS ARE GIVEN FROM FACE OF FINISH SURFACE, U.N.O.

I. ALIGN TOP OF ALL ADJACENT WINDOW AND DOOR HEADERS, U.N.O.

### 2. TRUSSES

A. THE GENERAL CONTRACTOR SHALL HAVE THE CITY APPROVED TRUSS PLANS ON THE JOB SITE PRIOR TO FOUNDATION INSPECTION. THE TRUSS MANUFACTURER SHALL SUBMIT CALCULATIONS, SHOP DRAWINGS, DETAILS, BRIDGING AND ERECTION BRACING SIGNED BY A REGISTERED ENGINEER TO THE BUILDING DEPARTMENT AND STRUCTURAL ENGINEER FOR THEIR REVIEW PRIOR TO FABRICATION.

B. TRUSS MANUFACTURERS SHALL PROVIDE MEMBERS OF ADEQUATE BEARING AREA IN SUCH A WIDTH TO INSURE AGAINST OVERSTRESSING OF SUPPORTING MEMBERS, MULTIPLE JOISTS, GIRDSERS & PLATES OR PROVIDE BEARING PLATES & DETAILS TO DO THE SAME.

C. THE GENERAL CONTRACTOR SHALL COORDINATE WITH THE TRUSS MANUFACTURER, FRAMING, ELECTRICAL, PLUMBING AND MECHANICAL CONTRACTORS AT FIRE PROTECTED AREAS TO MAINTAIN REQUIRED FIRE PROTECTION WITHOUT PENETRATIONS UNLESS ALLOWED BY CODE AND LOCAL JURISDICTION.

## FINISH CARPENTRY & WOODWORK

1. EXTERIOR SIDING SHALL BE PRIMED, CEMENT FIBER SIMILAR TO JAMES HARDIE HARDIPANEL, INCLUDING ALL BOARD TRIM (3/4" THICKNESS) & BATTENS TEXTURE TO BE RUSTIC.
2. PROVIDE ALL NECESSARY BLOCKING NAILERS, FASTENERS & TRIM AS REQUIRED FOR A COMPLETE & SECURE INSTALLATION.

## ABBREVIATIONS

<b>ABV</b> - ABOVE	<b>BITUM</b> - BITUMINOUS	<b>CT</b> - CERAMIC TILE	<b>EW</b> - EACH WAY	<b>FT</b> - FOOT, FEET	<b>IN</b> - INCH
<b>ACOUS</b> - ACOUSTICAL	<b>BLK</b> - BLOCK	<b>CIR</b> - CIRCLE	<b>E</b> - EAST	<b>FTG</b> - FOOTING	<b>INCL</b> - INCLUDE
<b>ADDL</b> - ADDITIONAL	<b>BLKG</b> - BLOCKING	<b>CLR</b> - CLEAR	<b>EL</b> - ELEVATION	<b>FND</b> - FOUNDATION	<b>ID</b> - INSIDE DIAMETER
<b>ADH</b> - ADHESIVE	<b>BLW</b> - BELOW	<b>COL</b> - COLUMN	<b>ELEV</b> - ELEVATION	<b>FRM</b> - FRAM(D), (ING)	<b>INS</b> - INSULATE
<b>ADJ</b> - ADJUSTABLE	<b>BTW</b> - BETWEEN	<b>CONC</b> - CONCRETE	<b>EQ</b> - EQUAL	<b>FBO</b> - FURNISHED BY OTHERS	<b>INT</b> - INTERIOR
<b>AFF</b> - ABOVE FINISH FLOOR	<b>BOT</b> - BOTTOM	<b>CMU</b> - CONCRETE MASONRY UNIT	<b>EQV</b> - EQUIVALENT	<b>FUR</b> - FURRED	<b>INV</b> - INVERT
<b>AGG</b> - AGGREGATE	<b>BLDG</b> - BUILDING	<b>CORR</b> - CORRUGATED	<b>EXCV</b> - EXCAVATE	<b>GA</b> - GAGE, GAUGE	<b>JNT</b> - JOINT
<b>A/C</b> - AIR CONDITIONING	<b>B/O</b> - BY OTHERS	<b>CRPT</b> - CARPET	<b>EXH</b> - EXHAUST	<b>GAL</b> - GALLON	<b>JST</b> - JOIST
<b>ALT</b> - ALTERNATE	<b>BO</b> - BOTTOM OF		<b>EXG</b> - EXISTING	<b>GL</b> - GLASS, GLAZING	
<b>ALUM</b> - ALUMINUM	<b>BOH</b> - BOTTOM OF HEADER		<b>EXT</b> - EXTERIOR	<b>GLBK</b> - GLASS BLOCK	
<b>ANOD</b> - ANODIZED		<b>DTL</b> - DETAIL		<b>GLB</b> - GLUE LAMINATED BEAM	
<b>APX</b> - APPROXIMATE	<b>CAB</b> - CABINET	<b>DIA</b> - DIAMETER	<b>FBD</b> - FIBERBOARD	<b>GT</b> - GROUT	<b>KD</b> - KILN DRIED
<b>APT</b> - APARTMENT	<b>CALC</b> - CALCULATION	<b>DIM</b> - DIMENSION	<b>FCB</b> - FIBER CEMENT BOARD	<b>GRD</b> - GRADE, GRADING	<b>KIT</b> - KITCHEN
<b>ARCH</b> - ARCHITECT	<b>CH</b> - CEILING HEIGHT	<b>DW</b> - DISHWASHER	<b>FGL</b> - FIBERGLASS	<b>GWB</b> - GYPSUM WALL BOARD	<b>LB</b> - POUND
<b>ASPH</b> - ASPHALT	<b>CL</b> - CENTERLINE	<b>DIV</b> - DIVISION	<b>FIN</b> - FINISH		<b>LAM</b> - LAMINATE(D)
<b>AVE</b> - AVENUE	<b>CO</b> - CLEAN OUT	<b>DR</b> - DOOR	<b>FFE</b> - FINISHED FLOOR ELEVATION	<b>HWD</b> - HARDWARE	<b>LAV</b> - LAVATORY
<b>AVR</b> - AVERAGE	<b>CONTR</b> - CONTRACT (OR)	<b>DH</b> - DOUBLE HUNG	<b>FA</b> - FIRE ALARM	<b>HDR</b> - HEADER	<b>LH</b> - LEFT HAND
<b>AWN</b> - AWNING	<b>COORD</b> - COORDINATE	<b>DS</b> - DOWNSPOUT	<b>FE</b> - FIRE EXTINGUISHER	<b>HVAC</b> - HEATING, VENTILATION-AIR CONDITIONING	<b>L</b> - LENGTH
	<b>CIP</b> - CAST-IN-PLACE	<b>DRWR</b> - DRAWER	<b>FLSH</b> - FLASHING	<b>HT</b> - HEIGHT	<b>LVR</b> - LOUVER
	<b>CB</b> - CATCH BASIN	<b>DWG</b> - DRAWING	<b>FLR</b> - FLOOR	<b>HC</b> - HOLLOW CORE	
<b>BSMT</b> - BASEMENT	<b>CLG</b> - CEILING		<b>FLOR</b> - FLUORESCENT	<b>HOR</b> - HORIZONTAL	<b>MFR</b> - MANUFACTURER
<b>BM</b> - BEAM				<b>HB</b> - HOSE BIB	<b>MAX</b> - MAXIMUM

## EROSION CONTROL NOTES

1. INSTALL SILT FENCE PRIOR TO ANY EXCAVATION OR CONSTRUCTION.
2. MINIMIZE SITE DISTURBANCE BY TIGHT CONTROL OF EXCAVATION LIMITS.
3. ALL EXPOSED SOIL SHALL BE MULCHED WITH STRAW OR WOOD CHIPS TO MINIMIZE SOIL EROSION. NO SOIL SHALL BE LEFT IN AN EXPOSED CONDITION. IT IS RECOMMENDED THAT THE CONTRACTOR MAINTAIN A STOCK PILE OF THIS MATERIAL ON SITE FOR QUICK APPLICATION.
4. HYDROSEED WITH A WOOD CELLULOSE FIBER MULCH APPLIED AT A RATE OF 2,000#/ACRE. USE AN ORGANIC TACKIFIER AT NO LESS THAN 150 #/ACRE OR PER MANUFACTURE'S RECOMMENDATION IF HIGHER. APPLICATION OF TACKIFIER SHALL BE HEAVIER AT EDGES, IN VALLEYS AND AT CRESTS OF BANKS AND OTHER AREAS WHERE SEED CAN BE MOVED BY WIND OR WATER.
5. DISPERSION TRENCHES SHALL OVERFLOW ONTO NATIVE UNDISTURBED GROUND. NO SITE DISTURBANCE BELOW TRENCHES.
6. CONTRACTOR SHALL OBTAIN AND MAINTAIN AN EPSC PERMIT FROM THE CITY'S STORMWATER DEPARTMENT PRIOR TO THE START OF CONSTRUCTION.

## ROOFING, FLASHING & SEALANTS

1. PROVIDE ROOF PENETRATION FLASHING FOR ALL VENT THRU ROOF PENETRATIONS.
2. SHINGLE ROOFING SHALL BE DIMENSIONAL ASPHALT SHINGLES (MIN. 25 YEAR WARRANTY) OVER ROOFING FELTS AND ICE & WATER SHIELDS. PROVIDE 36" WIDE ICE & WATER SHIELD ALONG ALL EAVES, RIDGES & VALLEYS.
4. METAL ROOFING TO BE EITHER ALUMINUM OR GALVANIZED STEEL WITH APPROVED SNOW AND ICE GUARD RAILS WITH MATCHING PAINTED COATING.
5. SEALANTS SHALL BE PROVIDED AT JOINTS TO CREATE A WATERTIGHT CONDITION. PROVIDE CLOSED CELL POLYETHYLENE, FOAM BACKER ROD & JOINT FILLER AS NECESSARY. PROVIDE SEALANTS AS FOLLOWS:
  - A. GENERAL EXTERIOR JOINTS - MULTI-PART OR SINGLE COMPONENT NON-SAG URETHANE.
  - B. JOINTS AROUND PLUMBING FIXTURES & PIPE PENETRATION - MILDEW RESISTANT SILICONE SEALANT
  - C. JOINTS AROUND DOOR & WINDOW FRAMES PAINTABLE ACRYLIC EMULSION SEALANT
6. PROVIDE PRE-FINISHED SHEET ROOF DRAINAGE (GUTTER & DOWNSPOUT) ROOF EDGE FLASHING. RAKE FLASHING PER S.M.A.C.N.A. STANDARDS.
7. PROVIDE ALL TRIM FLASHING, SILL BLOCKING, FASTENERS & ACCESSORIES REQUIRED FOR A COMPLETE INSTALLATION.
8. ALL COLORS AND FINISHES TO BE SELECTED AND/OR VERFIED BY THE ARCHITECT, U.N.O.

## DOORS

1. DOORS SHALL BE PAINTED HOLLOW GALVANIZED METAL DOORS WITH PAINTED GALVANIZED METAL FRAMES. INTEGRATED GALV. STEEL LOUVERS WITH MATCHING FINISH AND COLOR TO BE PROVIDED IN DOORS SPECIFIED IN DRAWINGS AND SCHEDULES. PROVIDE GALV. INSECT SCREEN ON INSIDE OF DOOR LOUVER.
2. DOOR HARDWARE SHALL CONSIST OF A.D.A. COMPLIANT LEVER TRIM CYLINDRICAL LOCKSETS (CLASSROOM FUNCTION). MINIMUM 1-1/2 PAIR BUTT HINGES, DOOR STOPS, WEATHERSTRIPPING, CLOSERS, THRESHOLDS & OTHER HARDWARE APPROPRIATE FOR CONDITION. COORDINATE KEYING REQUIREMENTS WITH CLIENT. HARDWARE CONTRACTOR SHALL SUBMIT HARDWARE SCHEDULE & PRODUCT CUT SHEETS FOR REVIEW.
3. ALL DOORS TO BE 3'-0" x 7'-0" WITH 1" WIDE H.M. FRAMES WITH 4" HEAD, U.N.O.

## GYPSUM BOARD WORK

1. ALL GYPSUM BOARD TO BE 5/8" THICK, MOISTURE RESISTANT, U.N.O.
2. ALL WORK TO COMPLY WITH ASTM C754 & C840. TAPE AND FINISH ALL GYPSUM BOARD TO COMPLY WITH A LEVEL 4 FINISH (TAPED & TREATED PANEL JOINTS).
3. PROVIDE CORNER BEADS, J-BEADS & OTHER EDGE TRIM BASED UPON FIELD CONDITIONS AND INDUSTRY PRACTICES. PROVIDE CONTROL JOINTS WHERE REQUIRED FOR CRACK CONTROL.
4. CAULK JOINT BETWEEN GYPSUM BOARD & ADJACENT DISSIMILAR MATERIALS (CMU-WOOD) TYP.

## PAINTING

1. ALL OPAQUE FINISHED PAINTED SURFACES SHALL BE PAINTED WITH A PRIMER COAT PLUS (2) FINISH COATS APPLIED PER THE MANUFACTURER'S RECOMMENDATIONS FOR THE FILM THICKNESS. THE FOLLOWING SURFACES & MATERIALS SHALL RECEIVE AN OPAQUELY PAINTED FINISH:
  - A. GYPSUM BOARD WALLS, SOFFITS & CEILINGS
  - B. HOLLOW METAL DOORS & FRAMES
  - C. EXTERIOR TRIM NOT OTHERWISE INDICATED TO RECEIVE TRANSPARENT FINISH
2. PAINT SYSTEM SELECTED SHALL BE APPROPRIATE FOR SUBSTRATE EXPOSURE & CONDITIONS
3. PREFINISHED WOOD SHALL NOT BE FIELD PAINTED
4. ALL CONCRETE SLABS SHALL BE TREATED WITH COMBINATION CURE & SEAL TYPE SEALER.
5. TRANSPARENT FINISHED WOOD NOT OTHERWISE SHOP FINISHED BY FABRICATOR SHALL HAVE FINISH TO MATCH SHOP FINISH.

## TOILET ACCESSORIES & PARTITIONS

1. TOILET TISSUE DISPENSER EQUAL TO BOBRICK MODEL B-2888 CLASSIC SERIES SURFACE MOUNTED MULTI-ROLL TOILET TISSUE DISPENSER. MOUNT AT 24" ABOVE FINISH FLOOR (A.F.F) TO CENTERLINE (CL) & 8" FROM FRONT EDGE OF TOILET FIXTURE TO CL.
2. 1-1/4" DIA. SS GRAB BAR WITH CONCEALED FASTENERS & PEENED NON-SLIP SURFACE EQUAL TO BOBRICK AS INDICATED.
  - A. B-5806 x 18 MOUNTED VERTICAL AT 34" A.F.F. TO C.L. & 40" FROM REAR WALL TO C.L. & 40" ABOVE FLOOR TO BTM.
  - B. B-5806 x 36 MOUNTED HORIZONTAL AT 34" TO C.L. WITH END FACING SIDEWALL SET 12" FROM C.L. OF WATERCLOSET
  - C. B-5806 x 42 MOUNTED HORIZONTAL AT 34" A.F.F. TO C.L. WITH END SET 12" FROM REAR WALL
3. 18"x30" CHANNEL FRAMED MIRROR EQUAL TO BOBRICK MODEL B-165 1830 (TEMPERED GLAZING) LOCATE CENTERED ON LAVATORY AND 40" A.F.F. AND 40" A.F.F. TO BOTTOM OF MIRROR
4. ELECTRIC HAND DRYER EQUAL TO NOVA 5 MODEL 0122, 120 VOLT SURFACE MOUNTED HAND DRYER WITH BRUSHED CHROME FINISH. MOUNT AT 37" A.F.F. TO BTM. OF UNIT.
5. SURFACE-MOUNTED PAPER TOWEL DISPENSER EQUAL TO BOBRICK B-3559039 MOUNTED AT 37" A.F.F. TO BTM. OF UNIT.
6. SURFACE-MOUNTED PAPER SOAP DISPENSER EQUAL TO BOBRICK B-42 MOUNTED AT 37" A.F.F. TO BTM. OF UNIT.
7. SURFACE-MOUNTED BABY CHANGING STATION EQUAL TO BOBRICK KB200-00 MOUNTED AT 36" A.F.F. TO BT, OF UNIT.
8. FLOOR MOUNTED OVERHEAD BRACED POWDER COATED STEEL TOILET PARTITIONS AND URINAL SCREEN AND ASSOCIATED ACCESSORIES IN THE CONFIGURATION INDICATED IN THE DRAWINGS EQUAL TO PARTITIONS BY ACCURATE PARTITIONS CORP.

**MAS** - MASONRY  
**MECH** - MECHANIC(AL)  
**MED** - MEDIUM  
**MDF** - MEDIUM DENSITY FIBERBOARD  
**MDO** - MEDIUM DENSITY OVERLAY  
**MBR** - MEMBER  
**MMB** - MEMBRANE  
**MTL** - METAL  
**MIN** - MINIMUM  
**MIR** - MIRROR  
**MISC** - MISCELLANEOUS

**NOM** - NOMINAL  
**N** - NORTH  
**NIC** - NOT IN CONTRACT  
**NTS** - NOT TO SCALE  
**NO, #** - NUMBER  
**OBS** - OBSCURE  
**OC** - ON CENTER  
**OP** - OPAQUE  
**OPG** - OPENING  
**OSB** - ORIENTATED STRAND BOARD  
**OD** - OUTSIDE DIAMETER

**REF** - REFERENCE  
**RFL** - REFLECTED  
**REFR** - REF  
**RE** - REINFORCED

**REQ'D** - REQUIRED  
**REV** - REVISION  
**R** - RISER  
**R&S** - ROD AND SHELF  
**RFG** - ROOFING  
**RM** - ROOM  
**RO** - ROUGH OPENING

**SCH** - SCHEDULE  
**SCN** - SCREEN  
**SHTH** - SHEATHING  
**SHT** - SHEET  
**SH** - SHELF, SHELVING  
**SIM** - SIMILAR  
**S** - SOUTH  
**SLB** - SLAB  
**SPEC** - SPECIFICATION  
**STD** - STANDARD  
**STL** - STEEL  
**STR** - STRUCTURAL  
**SA** - SUPPLY AIR  
**SS** - STAINLESS STEEL  
**SYS** - SYSTEM

**TEL** - TELEPHONE  
**TEMP** - TEMPERED  
**T&G** - TONGUE AND GROOVE  
**T/O** - TOP OF  
**T** - TREAD  
**TYP** - TYPICAL


**UC** - UNDER COUNTER  
**UNF** - UNFINISHED  
**UNO** - UNLESS NOTED OTHERWISE

**VB** - VAPOR BARRIER  
**VER** - VERIFY  
**VIF** - VERIFY IN FIELD  
**VERT** - VERTICAL  
**VIN** - VINYL SHEET

**WL** - WALL  
**WC** - WATER CLOSET  
**WH** - WATER HEATER  
**WP** - WATER PROOFING  
**WR** - WEATHER RESISTANT



### REVISIONS



### DOCUMENT PHASE CONSTRUCTION DOCUMENTS

### DATE ISSUED

08 / 15 / 17

### GENERAL CONDITIONS, SPECIFICATIONS & ABBREVIATIONS

**A0.2**